



Special features

- Ideal for high-quality illumination of individual workstations
- Redesigned and extended lamp head for optimal illumination of 160x80 cm tables
- Direct and indirect light can be dimmed and switched separately using touch panel
- Light colour adjustable via touch panel
- High-precision radar presence detector detects the smallest movements
- Daylight sensor for dynamic brightness adjustment

Housing Material	Aluminium
Housing Color	White
Material of Lens	Polycarbonate - PC
Protection Class	Protection class I/ protective grounding
Rated Input	80 W
Rated Power Consumption Standby	0.5
Rated Power Consumption Network Standby	0.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Primary Connection	Safety plug
Primary Cable Length	2.5 m
Connection Type According to Standard	Typ X
Dimmable	Yes
Control	Touch-Sensor
Motion Detector	Yes
Kind of Motion Detector	Presence detector
Detection Distance	3-3.5 m
Angle of Detection	85 Degree
Motion detector changeable	Yes
Adjustable brightness threshold	No
Adjustable follow-up time	No

UGR	6
Light Exit Surfaces	2
Light characteristics	Direct, Indirect
Light direction	Top, Below
Length	1240 mm
Width	64 mm
Height	1950 mm
Base length	530 mm
Base width	225 mm
Base height	10 mm
Product weight	11655 g

Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 20
IK Protection Class	IK06
Life Time L80 / B10	50000 h
Life Time L80 / B50	50000 h
Switching Cycles	100000
Power Consumption	80 kWh/1000h
Energy Efficiency Class Lightsource	This product contains light sources of energy efficiency classes D and F.

Light Source	LED, Light source changeable TC
Lightcolor	Neutral white
Color Temperature	4000 K
Colour Consistency	3 SDCM
Colour consistency light source	3 SDCM
Colour Rendering Index (Ra)	95
Rated Luminous Flux	10100 lm
Luminous Efficiency	126.3 lm/W
Rated Angle of Reflection	120 Degree
Rated Angle of Reflection 2	50 Degree