



This pendant lamp is distinct for its transparent luminous element. The surface is almost completely see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare. This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light stands out in any type of office environment.

**Special features**

- Very low glare value
- Transparent luminous element
- Max. suspended mounting 1,500 mm

|  |   |
|--|---|
| <b>Housing Material</b>                | Aluminium                                 |
| <b>Housing Color</b>                   | White                                     |
| <b>Material of Lens</b>                | PMMA                                      |
| <b>Protection Class</b>                | Protection class I/protective grounding   |
| <b>Rated Input</b>                     | 50 W                                      |
| <b>Rated Power Consumption Standby</b> | 0.5 W                                     |
| <b>Rated Input Voltage Frequency</b>   | 200-240 V/AC 50 / 60 Hz                   |
| <b>Power Supply Unit incl.</b>         | Yes                                       |
| <b>Connection Type</b>                 | Clamp                                     |
| <b>Dimmable</b>                        | Yes                                       |
| <b>Control</b>                         | Leading-edge dimmer, Trailing-edge dimmer |
| <b>Motion Detector</b>                 | No  |

|  |  |
|--|--|
| <b>Working Temperature</b>                 | -10 to 55 °C   |
| <b>Storage Temperature</b>                 | -20 to 60 °C   |
| <b>IP Protection Class</b>                 | IP 40  |
| <b>IK Protection Class</b>                 | IK04   |
| <b>Life Time L70 / B50</b>                 | 75000 h  |
| <b>Life Time L80 / B10</b>                 | 50000 h  |
| <b>Life Time L80 / B50</b>                 | 60000 h  |
| <b>Power Consumption</b>                   | 50 kWh/1000h   |
| <b>Energy Efficiency Class Lightsource</b> | This product contains a light source of energy efficiency class C. |

|                                    |                                 |
|------------------------------------|---------------------------------|
| <b>Light Source</b>                | LED, Light source changeable TC |
| <b>Color Temperature</b>           | 3000/3500/4000 K                |
| <b>Colour Consistency</b>          | 5 SDCM                          |
| <b>Colour Rendering Index (Ra)</b> | 90                              |
| <b>Rated Luminous Flux</b>         | 6200/6400/6400 lm               |
| <b>Rated Angle of Reflection</b>   | 140 Degree                      |
| <b>Rated Angle of Reflection 2</b> | 150 Degree                      |
| <b>UGR</b>                         | 22                              |
| <b>Light Distribution</b>          | Symmetric                       |

|                              |                  |
|------------------------------|------------------|
| <b>Light Exit Surfaces</b>   | 1                |
| <b>Light characteristics</b> | Direct, Indirect |
| <b>Light direction</b>       | Top, Below       |

|                             |         |
|-----------------------------|---------|
| <b>Height</b>               | 12 mm   |
| <b>Diameter</b>             | 633 mm  |
| <b>Base height</b>          | 43 mm   |
| <b>Base diameter</b>        | 215 mm  |
| <b>Pendulum Length max.</b> | 1800 mm |

