



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Round ceiling recessed downlight made from die-cast aluminium; adjustable; for trimless installation; surface White Matt; powder coated; matt texture; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90; beam angle 31°; 360° rotatable and 35° tiltable; degree of protection IP20; Class 3; to be combined with the plasterkit suitable for ceiling thickness; driver not included; optional honeycomb louver available, to reduce glare;



LUMINAIRE

Ceiling _____
 Recessed _____
 tilt max 35 ° _____
 rotation 360 ° _____
 White Matt _____
 IP20 _____
 Interior _____
 440 lm _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 ≤ 2 SDCM (initial MacAdam) _____

Optical

beam angle 31° _____

Electrical

excl. driver _____
 18 V _____
 system 5.0 W _____
 Class III _____
 Standard _____

Physical

diameter 73 mm _____
 height 35 mm _____
 0.14 kg _____
 alu plasterkit _____

Cutout

diameter 78-80 mm _____
 min. ceiling thickness 12.5 mm _____
 max. ceiling thickness 25 mm _____
 recessed depth 80 mm _____

[198261W5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
5W 250mA 12-21V phase-cut dim			68-33-22	90226201
10W 250mA 10-40V DALI-2 push dim			166-29-21	90246403

OPTICAL ACCESSORIES

Honeycomb Louver

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK petit CENO LECA PIRRO QITO	Black		29	915230B0