



The ALWAID 2 recessed wall light fits into any 68 mm standard or deep switch box thanks to its compact design. Furthermore, it does not require an additional power supply. The variety of covers allows you to find a style that suits your space and illuminates your surroundings with beautiful indirect light. The article includes the base only; covers are not included in the scope of delivery.

Special features

- 230 V direct connection
- Feed-through wiring possible
- Can be dimmed using leading-edge phase dimmers or trailing-edge phase dimmers
- Suitable for 68 mm standard and deep switch boxes

| | |
|--------------------------------------|---|
| Housing Material | Aluminium |
| Housing Color | White |
| Protection Class | Protection class I/protective grounding |
| Rated Input | 4.8 W |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz |
| Power Supply Unit incl. | No |
| Dimmable | Yes |
| Control | Trailing-edge dimmer |
| Motion Detector | No |

| | |
|--|--|
| Switching Cycles | 50000 |
| Power Consumption | 5 kWh/1000h |
| Energy Efficiency Class Lightsource | This product contains a light source of energy efficiency class G. |

| | |
|--|----------------------------------|
| Light Source | LED, Light source not changeable |
| Color Temperature | 2700 K |
| Colour Consistency | 3 SDCM |
| Colour consistency light source | 3 SDCM |
| CRI (Ra) | 90 |
| Rated Luminous Flux | 200 lm |
| Luminous Efficiency | 41.6 lm/W |
| Rated Angle of Reflection | 100 Degree |
| UGR | 19 |

| | |
|---------------------------|---------|
| Height | 39.9 mm |
| Diameter | 71.2 mm |
| Installation Depth | 39.9 mm |
| Cut Out Diameter | 61.5 mm |
| Product weight | 73 g |

| | |
|----------------------------|--------------|
| Working Temperature | -10 to 55 °C |
| Storage Temperature | -60 to 20 °C |
| IP Protection Class | IP 20 |

| | |
|----------------------------|---------|
| Life Time L70 / B50 | 75000 h |
| Life Time L80 / B10 | 50000 h |
| Life Time L80 / B50 | 60000 h |

