



Housing Material	Plastic
Housing Color	White
Housing Surface	Matt
Material of Lens	Plastic
Colour of Lens	White
Protection Class	Protection class I/protective grounding
Rated Input	30 W
Rated Input Voltage min./max.	220-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Connection Type	Adapter
Control	No
Motion Detector	No

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	54000 h
Switching Cycles	30000
Power Consumption	30 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Lightcolor	Warm white (WW)
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	2525 lm
Luminous Efficiency	84.17 lm/W
Rated Angle of Reflection	40 Degree
UGR	19
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	350 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	210 mm
Diameter	90 mm
Product weight	860 g

