



Special features

- Can be rotated and swivelled
- Large tilt angle
- High luminous flux
- Housing made from die-cast aluminium

Housing Material	Die-cast aluminium	Storage Temperature	-10 to 40 °C
Housing Color	White	IP Protection Class	IP 20
Material of Lens	Glass	IK Protection Class	IK07
Protection Class	Protection class I/protective grounding	Life Time L70 / B50	30000 h
Rated Input	30 W	Switching Cycles	15000
Rated Input Voltage min./max.	220-240 V/AC 50 / 60 Hz	Power Consumption	30 kWh/1000h
Frequency		Energy Efficiency Class	F
Power Supply Unit incl.	Yes		
Connection Type	Adapter		
Control	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Lightcolor	Neutral white		
Color Temperature	4000 K		
Colour Consistency	5 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3300 lm		
Luminous Efficiency	110 lm/W		
Rated Angle of Reflection	90 Degree		
UGR	28		
Distribution Characteristic 120°	DLS		
Swivel Angle	180 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Depth	261 mm		
Width	236 mm		
Height	41 mm		
Product weight	1550 g		
Working Temperature	-20 to 40 °C		