



Housing Material	Aluminium	IK Protection Class	IK03
Housing Color	White	Life Time L70 / B50	60000 h
Material of Lens	PMMA	Life Time L80 / B50	60000 h
Protection Class	Protection class I/ protective grounding	Switching Cycles	100000
Rated Input	50 W	Power Consumption	50 kWh/1000h
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class B.
Power Supply Unit incl.	Yes		
Connection Type	Adapter		
Control	No		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Lightcolor	Neutral white		
Color Temperature	4000 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	7250 lm		
Rated Angle of Reflection	30 Degree		
Rated Angle of Reflection 2	90 Degree		
Light Distribution	Symmetric		
Light Exit Surfaces	3		
Light characteristics	Direct		
Light direction	Below		
Depth	1493 mm		
Width	120 mm		
Height	68 mm		
Product weight	2150 g		
Working Temperature	-25 to 40 °C		
Storage Temperature	-40 to 85 °C		
IP Protection Class	IP 20		