



Housing Material	PP - Polypropylene	Life Time L70 / B50	50000 h
Housing Color	Black	Switching Cycles	100000
Housing Surface	Matt	Power Consumption	3 kWh/1000h
Colour of Lens	White	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class C.
Surface Structure of Lens	Opal		
Protection Class	Protection class II/ protective insulation		
Rated Input	3 W		
Rated Input Voltage min./max. Frequency	200-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Control	No		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	250/260 lm		
Rated Luminous Flux 2	260 lm		
Rated Angle of Reflection	120 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Front		
Depth	275 mm		
Width	275 mm		
Height	64 mm		
Working Temperature	-20 to 50 °C		
Storage Temperature	-20 to 60 °C		
IP Protection Class	IP 54		
IK Protection Class	IK08		