



The ceiling lights from the LUCEA series with CCT are available with outputs of 6, 10, 15, 20 and 30 W. They provide up to 2,900 lumens of light output depending on the version. The light emission angle can be narrowed or expanded by changing the optionally available lenses. A CCT switch allows the colour temperature to be set to one of two levels.

Special features

- Incl. black reflector ring
- Comprehensive range of accessories for customisation
- Light colour adjustable in two steps

Housing Material	Aluminium	Working Temperature	-20 to 40 °C
Housing Color	White	Storage Temperature	-20 to 65 °C
Material of Lens	PMMA	IP Protection Class	IP 20
Halogen free	No	IK Protection Class	IK03
Protection Class	Protection class I/protective grounding	Life Time L70 / B50	50000 h
Rated Input	20 W	Switching Cycles	100000
Rated Power Consumption Standby	0.5 W	Power Consumption	20 kWh/1000h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Power Supply Unit incl.	Yes		
Dimmable	Yes		
Control	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	5 SDCM		
Colour consistency light source	5 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	1930/2000 lm		
Rated Angle of Reflection	36 Degree		
UGR	14		
Distribution Characteristic 120°	DLS		
Swivel Angle	90 Degree		
Rotation Angle	350 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	241 mm		
Diameter	85 mm		

